

## MATERIAL SAFETY DATA SHEET

### SURECOTE 200.A.COLOUR

Infosafe™ NLYBA Issue Date July 2006 Status ISSUED by BS: 1.9.12  
No. NUPCP

#### Resins 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** SURECOTE 200.A.COLOUR  
**Product Code** B1SECRSC  
**Company Name** Nuplex Products.  
Pty Ltd  
**Address** 12 Industry Rd, Penrose, Auckland  
**Emergency Tel.** 1800 022 037 (24H)  
**Telephone/Fax Number** Tel: (09) 579 2029  
Fax: (09) 525 1618  
**Composites Recommended Use** Flooring compound.  
**Other Names** Not Available  
**Other Information** NEW ZEALAND: Nuplex Industries Ltd.  
12 Industry Road, Penrose,  
Auckland  
Phone: (09) 579 2029 Fax: (09) 525  
1618  
Emergency Advice (NZ): Phone: 0800 154 666

#### 2. HAZARDS IDENTIFICATION

##### Hazard Classification

Australia:  
Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia.  
Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.  
New Zealand:  
Classified as Hazardous according to the New Zealand Hazardous Regulations 2001.  
Classified as Dangerous Goods for transport, according to the New Zealand Standard NZS 5433:1999 Transport of Dangerous Goods on Land.

**Risk Phrase(s)**

R43 May cause sensitization by skin contact.  
 R36/38 Irritating to eyes and skin.  
 R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety Phrase (s)**

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 S28 After contact with skin, wash immediately with plenty of soap and water.  
 S61 Avoid release to the environment. Refer to special instructions/safety data sheet.  
 S24/25 Avoid contact with skin and eyes.  
 S37/39 Wear suitable gloves and eye/face protection.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Epoxy Resin (number average molecular weight <= 700)	25068-38-6	60-70 %
	Butanedioldiglycidyl ether	2425-79-8	0-10 %
	Ingredients determined not to be hazardous		Balance to 100%
	Bisphenol F-epichlorohydrin resin with Number Average Molecular Weight <700	28064-14-4	10-30 %

### 4. FIRST AID MEASURES

<b>Inhalation</b>	Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a face mask if breathing is difficult. Apply artificial respiration if not breathing. Seek medical attention.
<b>Ingestion</b>	Do not induce vomiting. Wash out mouth with copious amounts of water. Seek medical attention.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Wash contaminated clothing before re-use. If irritation occurs seek medical advice.
<b>Eye</b>	If contact with the eye(s) occur, wash with running water holding eyelid(s) open. Take care not to rinse contaminated water into the non-affected eye. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**First Aid**

<b>Facilities</b>	Eye wash and normal washroom facilities.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>Other Information</b>	For advice, contact a Poisons Information Centre (Phone eg Australia 131 126) or a doctor at once.

## 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use carbon dioxide, dry chemical, and foam or water mist.
<b>Hazards from Combustion Products</b>	Under fire conditions this product may emit toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
<b>Hazchem Code</b>	2X
<b>Precautions in connection with Fire</b>	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode.
<b>Unsuitable Extinguishing Media</b>	Water in a jet.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Emergency Procedures</b>	Wear appropriate personal protective equipment and clothing to minimise exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unnecessary personnel. If possible contain the spill. Place inert absorbent material onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to federal, Environmental Protection Authority and state regulations. If the spillage enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.
-----------------------------	--

## 7. HANDLING AND STORAGE

<b>Precautions for Safe Handling</b>	Use in a well ventilated area. DO NOT store or use in confined spaces. Build up of mists or vapours in the atmosphere must be prevented. Avoid breathing in spray or mists or vapours. Do not use near welding or other ignition sources and avoid sparks. Do not smoke. When dealing with this product, repeated or prolonged skin exposure without protection should be prevented in order to lessen the possibility of skin disorders. It is essential that all who come into contact with this material maintain high standards of personal hygiene ie. Washing hands prior to eating, drinking, smoking or using toilet facilities.
--------------------------------------	--

**Conditions for Safe Storage** Classified as a Class C2 (COMBUSTIBLE LIQUID) for the purposes of storage and handling. Store in a cool, dry well-ventilated area away from heat, sources of ignition, oxidising agents, foodstuffs, and clothing and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Do NOT pressurise, cut, heat or weld containers as they may contain hazardous residues. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**National Exposure Standards** No exposure standards have been established for this material by the Australian National Occupational Health & Safety Commission (NOHSC) or the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to any chemical may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.

**Biological Limit Values** No biological limit allocated.

**Engineering Controls** Good ventilation adequate to maintain the airborne contamination below target levels or exposure standards is required. The use of a local exhaust ventilation system (drawing vapours/mists away from workers breathing zone) is recommended. If the engineering controls are not sufficient to maintain concentrations of particulates and vapours below the exposure standards, suitable respiratory protection must be worn.

**Respiratory Protection** If engineering controls are not effective in controlling airborne exposure then respiratory protective equipment should be used suitable for protecting against airborne contaminants. Final choice of appropriate breathing protection is dependant upon actual airborne concentrations and the type of breathing protection required will vary according to individual circumstances. Expert advice may be required to make this decision. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices.

**Eye Protection** Safety glasses with side shields, goggles or full-face shield as appropriate recommended. Final choice of appropriate eye/face protection will vary according to individual circumstances i.e. methods of handling or engineering controls and according to risk assessments undertaken. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

**Hand Protection** Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

**Body Protection** Suitable work wear should be worn to protect personal clothing,

eg cotton overalls buttoned at neck and wrist. When large quantities are handled the use of plastic aprons and rubber boots is recommended. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance** Coloured thick liquid.

**Odour** Not available.

**Melting Point** Not available.

**Boiling Point** Not available.

**Solubility in Water** Insoluble.

**Specific Gravity** 1.506

**pH Value** Not available.

**Vapour Pressure** Not available.

**Vapour Density (Air=1)** Not available.

**Viscosity** 2600 cP

**Flash Point** >150°C

**Auto-Ignition Temperature** Not available.

**Flammable Limits - Lower** Not available.

**Flammable Limits - Upper** Not available.

---

## 10. STABILITY AND REACTIVITY

---

**Chemical Stability** Stable under normal conditions.

**Conditions to Avoid** Heat, direct sunlight, open flames or other sources of ignition.

**Incompatible Materials** Bisphenol A and F:  
 Reacts with strong oxidising agents. Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda. Reacts exothermically with bases (eg caustic soda), ammonia, primary and secondary amines, alcohols and acids.

**Hazardous**

**Decomposition Products** Thermal decomposition may result in the release of toxic and/or irritating fumes.

**Hazardous Polymerization** Bisphenol A and F:  
Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above. Polymerises in contact with caustic soda.

---

## 11. TOXICOLOGICAL INFORMATION

---

**Inhalation** Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

**Ingestion** Ingestion of this product may cause irritation to the gastric tract and upper respiratory tract, causing nausea, diarrhoea and vomiting.

**Skin** Will cause irritation in contact with skin, resulting in redness, itching and dermatitis. May cause sensitisation by skin contact.

**Eye** Irritating to eyes. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

**Chronic Effects** Prolonged or repeated skin contact may lead to allergic contact dermatitis and sensitisation in some individuals.

---

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability** No data is available for this material.

**Mobility** No data is available for this material.

**Environment Protection** Do not allow product to enter drains, waterways or sewers.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal Considerations** Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

---

## 14. TRANSPORT INFORMATION

---

**Transport** Australia:

**Information** This material is classified as a Class 9 (Miscellaneous Dangerous Goods) Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Dangerous goods of Class 9 (Miscellaneous Dangerous Goods) are incompatible in a placard load with any of the following:

- Class 1, Explosive
- Class 5.1, if the Class 9 substance is a fire risk substance
- Class 5.2, if the Class 9 substance is a fire risk substance

New Zealand:

This material is classified as a Class 9 - Miscellaneous Substance according to NZS 5433:1999 Transport of Dangerous Goods on Land.

Must not be loaded in the same freight container or on the same vehicle with:

- Class 1, Explosives

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:

(Note 3; Segregation devices may be used as to segregate dangerous goods of Class 9 when the nature of those dangerous goods requires them to be segregated from dangerous goods of);

- Class 3, Flammable liquids
- Class 4.1, Flammable solids
- Class 4.2, Spontaneously combustible substances
- Class 4.3, Dangerous when wet substances
- Class 5.1, Oxidising substances
- Class 5.2, Organic peroxides
- Class 6.1, Toxic substances
- Class 6.2, Infectious substances
- Class 8, Corrosive substances

And are incompatible with food and food packaging in any quantity.

<b>U.N. Number</b>	3082
<b>Proper Shipping Name</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. - (CONTAINS BISPHENOL A AND BISPHENOL F EPOXY RESINS)
<b>DG Class</b>	9
<b>Hazchem Code</b>	2X
<b>Packaging Method</b>	3.8.9
<b>Packing Group</b>	III
<b>EPG Number</b>	9C1
<b>IERG Number</b>	47

---

## 15. REGULATORY INFORMATION

---

**Regulatory Information** Australia:  
Classified as hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC).  
Poison Schedule: Schedule 5

New Zealand:  
Classified as Hazardous according to the Hazardous Substances

(Classification) Regulations 2001.  
Not scheduled according to the Toxic Substances Regulations  
1983.

**Poisons  
Schedule** S5

S5 New Zealand:Not Scheduled

**Hazard Category** Irritant,Dangerous for the environment

---

## 16. OTHER INFORMATION

---

**Date of  
preparation or  
last revision  
of MSDS**

MSDS created: July 2006.

**Contact  
Person/Point**

Australia: Business Hours: Mr Paul Verren  
Telephone: (02) 9839 4024  
Emergency Tel: 1800 022 037

New Zealand: Business Hours: Technical Manager  
(09) 279 2029  
Emergency Tel: 0800 154 666.

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Nuplex Industries (Aust) Pty Ltd. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

---

End of MSDS

---

(C) Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed on this site is the intellectual property of Acohs Pty Ltd.  
Copying of any MSDS displayed on this site is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed on this site cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.

Print Date: 12/02/2008

BS: 1.9.12

# MATERIAL SAFETY DATA SHEET

## SURECOTE 200 PART B STANDARD

Infosafe™ 1HL85      Issue Date June 2004      Status ISSUED by BS: 1.9.12  
No.      NUPCP

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### Resins

**Product Name** SURECOTE 200 PART B STANDARD

**Product Code** B82041

**Company Name** Nuplex Products  
Pty Ltd

**Address** 12 Industry Road, Penrose,  
New Zealand

**Emergency Tel.** 1800 022 037 (24H)

**Telephone/Fax Number** Tel: (09) 579 2029  
Fax: (09) 525 1618

**Composites Recommended Use** Curing agent for epoxy resins - flooring.

**Other Names** Not Available

**Other Information** NEW ZEALAND: Nuplex Industries Ltd.  
12 Industry Road, Penrose,  
Auckland  
Phone: (09) 579 2029 Fax: (09) 525  
1618  
Emergency Advice (NZ): Phone: 0800 154 666

### 2. HAZARDS IDENTIFICATION

#### Hazard Classification

HAZARDOUS SUBSTANCE.  
DANGEROUS GOODS.

Hazard classification according to the criteria of NOHSC.  
Dangerous goods classification according to the Australia  
Dangerous Goods Code.

#### Risk Phrase(s)

R34 Causes burns.  
R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.  
 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
 R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

**Safety Phrase (s)** S20 When using do not eat or drink.  
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 S38 If insufficient ventilation, wear suitable respiratory equipment.  
 S23(2) Do not breathe vapour.  
 S24/25 Avoid contact with skin and eyes.  
 S29/56 Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point.  
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

**Sensitization of Product** May cause sensitisation by skin contact.

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

Ingredients	Name	CAS	Proportion
	Isophorone diamine	2855-13-2	30-60 %
	Benzyl Alcohol	100-51-6	30-60 %
	Bisphenol A	80-05-7	1-9 %
	1,5-pentanediamine, 2-methyl	15520-10-2	1-9 %

---

### 4. FIRST AID MEASURES

---

**Inhalation** Remove the source of contamination or move the victim to fresh air. Ensure airways are clear, if breathing is difficult have qualified person give oxygen through a face mask. If not breathing apply artificial respiration. Seek immediate medical attention.

**Ingestion** Do not induce vomiting. Give 1-2 glasses of water to drink. In case of spontaneous vomiting, be sure that vomit can drain freely. Give nothing by mouth to an unconscious person. Seek immediate medical attention.

**Skin** Remove contaminated clothing. Wash affected skin areas with soap and water. Do not use solvents. If irritation persists seek medical attention.

**Eye** If contact with the eyes occurs, wash with copious amounts of water for at least 15 minutes holding eyelids open. Take care not to rinse contaminated water into the non-affected eye. Seek medical attention.

**First Aid Facilities** Eye wash fountains and safety showers should be easily accessible.

**Advice to Doctor** Treat symptomatically, for advice, contact the Poisons Information Centre (Australia 131 126; New Zealand 0800 POISON / 0800 764 766).

---

## 5. FIRE FIGHTING MEASURES

---

**Suitable Extinguishing Media**

Water mist, foam, carbon dioxide, dry powder.

**Specific Methods**

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes or products of combustion. Water spray may be used to cool down heat-exposed containers.

**Specific Hazards**

Product is combustible. Will burn in a general fire.

**Hazchem Code**

2X

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Spills & Disposal**

Clear area of all unprotected personnel. Wear appropriate protection equipment. Do not contaminate streams, rivers or water courses. Do not flush drains or sewers. Inform local authority if liquid enters drains, sewers, streams etc. Shut off sources of leak if safe to do so. Dike and contain spill with sand or earth.

MINOR: Absorb the liquid with sand, earth or other inert absorbent. Place used absorbent in suitable, sealable, labelled containers. Keep away from heat, naked flame or sparks.

MAJOR: Take up liquid with vacuum truck or absorb with sand, earth or other inert absorbent. Place used absorbent in suitable, sealable, labelled containers. Keep away from heat, naked flame or sparks.

---

## 7. HANDLING AND STORAGE

---

**Precautions for Safe Handling**

Wear appropriate protective equipment to prevent inhalation, skin and eye contact. Keep containers closed when not in use. Ensure a high level of personal hygiene is maintained when using this product. When using do not eat, drink or smoke.

**Conditions for Safe Storage**

Store in a cool, dry, well-ventilated area away from sources of heat or ignition. This product should be stored away from foodstuffs and strong oxidising agents. Keep containers closed at all times - check regularly for leaks.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

**National**

No exposure standards have been established for this material by

<b>Exposure Standards</b>	the Australian National Occupational Health & Safety Commission (NOHSC) or the Occupational Safety and Health Service (OSH) of the New Zealand Department of Labour. However, over-exposure to any chemical may result in enhancement of pre-existing adverse medical conditions and/or allergic reactions and should be kept to the least possible levels.
<b>Engineering Controls</b>	A local and/or general exhaust ventilation system is recommended to keep employee exposures as low as possible. The use of a local exhaust ventilation system (drawing vapours/mists away from workers breathing zone) is preferred.
<b>Respiratory Protection</b>	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapour/mist filter should be used. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
<b>Eye Protection</b>	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
<b>Hand Protection</b>	Wear laminated film, nitrile or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves.
<b>Body Protection</b>	Suitable protective workwear should be worn when working with this material, e.g. cotton overalls buttoned at neck and wrist.
<b>Hygiene Measures</b>	Follow good working practice: handle with care, avoid ingestion, inhalation, eye or skin contact. Do not smoke while using this product. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.
<b>Other Information</b>	If cured product made from this material is cut or sanded, an appropriate dust mask should be worn, together with safety glasses or goggles.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Appearance</b>	Amber liquid with amine odour.
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	>200°C
<b>Solubility in Water</b>	Not soluble
<b>Specific Gravity</b>	1.0
<b>pH Value</b>	Not applicable
<b>Vapour Pressure</b>	Not available
<b>Evaporation Rate</b>	Not available

<b>Flash Point</b>	112°C
<b>Flammability</b>	Combustible liquid, Class C1.
<b>Auto-Ignition Temperature</b>	Not available
<b>Flammable Limits - Lower</b>	Not available
<b>Flammable Limits - Upper</b>	Not available

---

## 10. STABILITY AND REACTIVITY

---

<b>Chemical Stability</b>	Stable
<b>Incompatible Materials</b>	Strong oxidising agents, acids, bases and epoxies.
<b>Hazardous Decomposition Products</b>	Carbon monoxide, carbon dioxide, oxides of nitrogen, ammonia, amines, fumes and smoke.
<b>Hazardous Reactions</b>	Will react with strong acids to produce heat.
<b>Hazardous Polymerization</b>	Will not occur.

---

## 11. TOXICOLOGICAL INFORMATION

---

<b>Toxicology Information</b>	For Isophorone diamine: Oral LD50 (rat): 1990 mg/kg. For benzyl alcohol: Oral LD50 (rat): 1230-1660 mg/kg
<b>Inhalation</b>	Harmful by inhalation. Vapour can cause severe irritation to the respiratory tract. Excessive exposure may result in headache, dizziness, incoordination, fatigue, nausea, loss of appetite and loss of consciousness.
<b>Ingestion</b>	Harmful if swallowed. Product will cause gastric irritation, and burns to digestive tract.
<b>Skin</b>	Harmful in contact with the skin; absorption through skin may cause systemic injury. Also severely irritating in contact with skin. It may cause burns and blisters. It may cause sensitisation by skin contact.
<b>Eye</b>	Risk of serious damage to the eyes. The product is corrosive and severely irritating in contact with the eyes. Permanent corneal damage may result if not washed of immediately.
<b>Chronic Effects</b>	May cause sensitisation in susceptible individuals by skin contact. Allergic response and dermatitis or asthma like

symptoms may occur after a single significant exposure, and sensitisation may occur on a single exposure, or multiple minor exposures.

---

## 12. ECOLOGICAL INFORMATION

---

<b>Ecotoxicity</b>	Not available
<b>Persistence / Degradability</b>	Not available
<b>Mobility</b>	Not available
<b>Bioaccumulative Potential</b>	Not available
<b>Environment Protection</b>	Avoid contaminating waterways.

---

## 13. DISPOSAL CONSIDERATIONS

---

<b>Waste Disposal</b>	Dispose of in accordance with applicable local, state and federal regulations.
-----------------------	--

---

## 14. TRANSPORT INFORMATION

---

<b>Transport Information</b>	<p>Australia: This material is a Class 8 Corrosive Substance according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. Class 8 - Corrosive Substances are incompatible in a placard load with any of the following:</p> <ul style="list-style-type: none"><li>- Class 1, Explosives</li><li>- Class 4.3, Dangerous When Wet Substances</li><li>- Class 5.1, Oxidising Agents &amp; Class 5.2 - Organic Peroxides</li><li>- Class 6, Toxic Substances (where the Toxic substances are cyanides and the corrosives are acids),</li><li>- Class 7, Radioactive Substances</li></ul> <p>and are incompatible with food and food packaging in any quantity.</p> <p>New Zealand: This material is classified as a Class 8 - Corrosive Substance according to NZS 5433:1999 Transport of Dangerous Goods on Land.</p> <p>Class 8 substances must not be loaded in the same freight container or on the same vehicle with:</p> <ul style="list-style-type: none"><li>- (Class 1) Explosives</li><li>- (Class 5.1) Oxidising substances</li><li>- (Class 5.2) Organic peroxides</li><li>- (Class 7) Radioactive materials unless specifically exempted and are incompatible with food and food packaging in any quantity.</li></ul> <p>Note 1; Cyanides (Class 6.1) must not be loaded in the same freight container or on the same vehicle with acids (Class 8).</p>
------------------------------	--

Note 2; Strong acids must not be loaded in the same freight container or on the same vehicle with strong alkalis. Packing Group I and II acids and alkalis should be considered as strong. Class 8 substances must not be loaded with in the same freight container; and on the same vehicle must be separated horizontally by at least 3 metres unless all but one are packed in separate freight containers with:

- (Class 4.3) Dangerous when wet substances

Goods of packing group II or III may be loaded in the same freight container or on the same vehicle if transported in segregation devices with:

- (Class 4.3) Dangerous when wet substances
- (Class 5.1) Oxidising substances
- (Class 5.2) Organic peroxides

and are incompatible with food and food packaging in any quantity.

<b>U.N. Number</b>	1760
<b>Proper Shipping Name</b>	CORROSIVE LIQUID, N.O.S. - (CONTAINS: ALIPHATIC AND ALICYCLIC AMINES)
<b>DG Class</b>	8
<b>Hazchem Code</b>	2X
<b>Special Precautions for User</b>	IMDG 8.
<b>Packaging Method</b>	3.8.8
<b>Packing Group</b>	III
<b>EPG Number</b>	8A1
<b>IERG Number</b>	37

---

## 15. REGULATORY INFORMATION

---

<b>Regulatory Information</b>	Poison Schedule (Australia): S5 Poison Schedule (New Zealand): Not Scheduled
<b>Poisons Schedule</b>	S5  S5 ; New Zealand:Not Scheduled
<b>Packaging &amp; Labelling</b>	Class 8 labels in accordance with the Australian Code for the Transport of Dangerous Goods, including Schedule 5 Poison requirements.
<b>Hazard Category</b>	Harmful, Corrosive

---

## 16. OTHER INFORMATION

---

**Date of  
preparation or  
last revision  
of MSDS**

MSDS Review: June 2004  
Supersedes: August 1999

**Contact  
Person/Point**

Australia: Business Hours: Mr Paul Verren  
Telephone: (02) 9839 4024  
Emergency Tel: 1800 022 037

New Zealand: Business Hours: Technical Manager  
(09) 279 2029  
Emergency Tel: 0800 154 666.

IMPORTANT ADVICE: This MSDS summarizes our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including its use in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Nuplex Industries (Aust) Pty Ltd. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

---

End of MSDS

---

(C) Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed on this site is the intellectual property of Acohs Pty Ltd.  
The compilation of MSDS's displayed on this site is the intellectual property of Acohs Pty Ltd. Copying of any MSDS displayed on this site is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed on this site cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.

Print Date: 12/02/2008

BS: 1.9.12