

MATERIAL SAFETY DATA SHEET

FOR PROFESSIONAL USE ONLY - KEEP OUT OF CHILDREN'S REACH

PRODUCED BY:

Protect Crete Pty Ltd
 14/137 Rooks Road
 Nunawading 3131
 Phone: + 61 3 9872 6172
 Fax : + 61 3 9872 6152
 24 Hours + 61 407 053 730
 www.protectcrete.com

SECTION 1: PRODUCT IDENTIFICATION

Product Name: MOISTURE-FIX 2
Formula: Proprietary

Hazard Rating:		Hazard Rating Scale:	
Health	2	Minimal	0
Fire	1	Slight	1
Reactivity	0	Moderate	2
Special	0	Serious	3
		Severe	4

SECTION 2: HAZARDOUS INGREDIENTS

Hazardous component (s): An insignificant trace of Butyl.

SECTION 3: PHYSICAL PROPERTIES

Physical Description: Milky-White, Liquid
Range: 7-8
Specific Gravity: 1.08

SECTION 4: FIRST AID MEASURES

INHALATION: MOISTURE-FIX 2 application indoors or outdoors requires no special ventilation. MOISTURE-FIX 2 spray is not hazardous to breathe; however, a mouth and nose dust mask should be worn while spraying anything onto set concrete surfaces, due to potential disturbance of sharp alkaline cement dust, or other particles which may become airborne.

EYES: Flush liberally with fresh water lifting upper and lower eye lids occasionally. Seek Medical attention if irritation develops.

INTERNAL: Drink plenty of water followed by induced vomiting, seek medical attention.

SECTION 5: HEALTH HAZARD INFORMATION

Primary routes of exposure: Eye and skin contact, inhalation, and ingestion.

SECTION 6: TOXICITY DATA

Toxicity: MOISTURE-FIX 2 is not toxic with normal incidental contact and/or prolonged exposure.

SECTION 7: PERSONAL PROTECTION

Protective Clothing: None required

Other protective measures: Protective eyewear is suggested, with an eyewash facility nearby.

SECTION 8: FIRE & EXPLOSIVE INFORMATION

Flammability: None

Extinguishing media: In case of surrounding fire involvement, water fog or dry foam is recommend.

SECTION 9: HAZARDOUS REACTIVITY

Stability: Stable

Hazardous decomposition products: CO, CO₂, NO_x

SECTION 10: DISPOSAL PROCEDURES

Spills or leaks: Dilute and flush with water where drain disposal is available. If accidentally discharged onto soil, do not flush, or allow Moisture-Fix 2 to drain into creek, lake or etc.

SECTION 11: SPECIAL PRECAUTIONS

Storage: Store inside or outside properly situated away from incompatible materials, i.e. strong acids. Temperature range 10 C to 28 C.

SECTION 12: ECOLOGICAL INFORMATION

Moisture-Fix 2 is environmentally neutral, and does not pose threat to the environment.

SECTION 13: DISCLAIMER

This MSDS should not be construed as product sales literature. Protect Crete Pty Ltd expressly disclaims all implied warranties or merchantability and fitness for particular purpose, with respect to the information provided herein.

SECTION 14: NOTICE

All information appearing herein is based upon data generated by Protect Crete Pty Ltd from recognized technical sources, and is believed to be accurate. MOISTURE-FIX 2 conditions of use are beyond Protect Crete Pty Ltd's control, and therefore, users are responsible to verify this data under their own operating conditions to determine whether MOISTURE-FIX 2 is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of MOISTURE-FIX 2, or from the publication or use of, or reliance upon, information contained herein. This information relates only to MOISTURE-FIX 2, and does not relate to its use in combination with any other material or in any other process.