

The new Ultra Max II 495 features the leading technology and performance of Graco's larger Ultra Max II models. The Ultra Max II 495 is the sprayer of choice for professionals who need a higher output sprayer for daily use on residential jobs.

Proven Endurance Pump

- Long-life V-Max Blue Packings, Chromex Rod, and Hardened Stainless Steel cylinder
- Hammer access inlet valve to inlet ball to easily clean or clear debris

SmartControl 2.0 Pressure Control

- Advanced microprocessor control delivers Graco's most consistent spray fan at all spraying pressures
- Zero deadband at lower spraying pressures makes the 495 ideal for fine finish spraying

Exclusive Brushless DC Motor

- Compact, light weight motor delivers higher horsepower per wall amp
- No brushes to replace
- Enclosed design protects internal motor components from dirt, dust and overspray to extend motor life

Chrome Plated, Welded Steel Hi-Boy cart

- Thick chrome over steel to withstand rugged environments
- Retractable handle doubles as a hose wrap
- TiltBack™ cart design
- Semi-pneumatic wheels roll easily over rough terrain

Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess

Ultra Max II 495



Hi-Boy Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
Ultra Max II 495 Stand	249915	.023	.54 (2.0)	3,300 (227)
Ultra Max II 495 Hi-Boy	249917	.023	.54 (2.0)	3,300 (227)
Ultra Max II 495 Lo-Boy	249916	.023	.54 (2.0)	3,300 (227)

Comes complete with: Contractor II Gun, RAC X LTX 517 Tip and Guard, 1/4 in x 50 ft (6.4 mm x 15.2 m) BlueMax II 3300 psi (227 bar) Hose.



Inlet tubes fit through 2-inch cap on standard 5-gallon buckets.



Endurance Pump with hammer access inlet valve.



Lo-Boy pail hook for easy bucket movement.