



# Ultra Max II 595

The Ultra Max II 595 is a workhorse. It's proven to be a hit with contractors who are looking for higher output and professional features, in a compact and portable sprayer.

## Proven Endurance Pump

- Long-life V-Max Blue Packings, Chromex Rod, and Hardened Stainless Steel cylinder
- Hammer access inlet to easily clean or clear debris

## SmartControl 2.0 Pressure Control

- Advanced microprocessor control delivers Graco's most consistent spray fan available at all spraying pressures
- Zero deadband at lower spraying pressures makes the 595 ideally suited for fine finish spraying

## Exclusive Brushless DC Motor

- Compact, light weight motor delivers higher horsepower per wall amp
- No brushes to replace
- Enclosed design protects internal motor components from dirt, dust, and overspray to extend motor life

## Chrome Plated, Welded Steel Lo-Boy Cart

- Low profile, compact design transports easily in tight spaces
- Retractable handle comfortably rolls behind you
- Integrated hose rack and pail hook for ultimate portability
- All metal swivel inlet suction hose with no-tools removal

## Easy Out Pump Filter

- Filtering reduces tip clogs and ensures a quality finish
- Easy Out design filters from the inside out – so filters won't get stuck or collapse when dirty
- Filter removes with the cap for less mess

## Swivel Inlet Suction Hose

- All aluminum construction is durable, light weight, and rust-free
- No-tools removal of hose for cleaning or accessing inlet ball
- Easily swivels to reach buckets or cans
- Stands upright so it won't tip over cans



Lo-Boy Unit Shown

DESCRIPTION	PART NUMBER	MAX TIP SIZE	MAX GPM (LPM)	MAX PSI (BAR)
Ultra Max II 595 Hi-Boy	249919	.025	0.6 (2.3)	3,300 (227)
Ultra Max II 595 Lo-Boy	249918	.025	0.6 (2.3)	3,300 (227)

Comes complete with: Contractor II Gun, RAC X LTX 517 Tip and Guard, 1/4 in x 50 ft (6.4 mm x 15.2 m) BlueMax II 3300 psi (227 bar) Hose.



TiHBack cart design (Hi-boy shown).



Inlet tube removes by hand for easy clean up.



Retractable handle for simple removal of coiled hose.